



Protect what matters most.



www.PipeBurstPro.com

## VIP Sr. Spec Sheet



### VIP Sr. Overview

VIP (Valve Interface Panel) Sr. is the executive controller for the PipeBurst Pro Sr. system. It communicates with all wired and wireless devices and controls the TickerValve. The VIP Sr. integrates with ionleaks.com, PipeBurst Pro's proprietary monitoring and control software.

### VIP Sr. Specs

Part #: VP200 (VIP Sr. with ionleaks.com)

- Dimensions: 6-3/4" W x 11-1/2" H x 5" D
- Power Source: 120v AC adapter with battery backup\*
- VIP Sr. Enclosure: Black Nylon Plastic
- Audible Notifications: Internal speaker
- Visual Notifications: Five bi-color LED lights (green/red)
- User Interface: Five push buttons matched with instructional label
- MultiValve Ready: Seven unique TickerValve operational modes
- FloMeter Compatible (x2)
- Alarm Contact Outputs (x2)
- Built-In Sensors: Internal freeze sensor
- Wireless Frequency: 433.92 MHz
- Wireless Range: 300 feet\*\*
- Wireless Device Capacity: Up to 63 unique devices



VIP Sr. (VP200)



### VIP Sr. Features

- With the instructional label displayed on the front panel, never search for the manual.
- One button TickerValve setup via AutoFind Mode.
- Monthly Valve Check ensures proper and continuous functionality of the TickerValve.
- Built-in freeze sensor triggers the alarm and closes the TickerValve at 41° Fahrenheit.
- Easy wireless device setup with one button sync.
- Installing extra wireless devices is quick and easy.
- Communicates with up to 63 serialized wireless devices providing expansive coverage.
- Comprehensive system monitoring and control with ionleaks.com via any internet capable device. (VIP Sr. includes an Ethernet port for standard connection)

\*12V Sealed Lead Acid Battery (SLAB)

\*\*Wireless range dependent on environmental factors including but not limited to building materials.

©2013 GreenField Direct, LLC rev.1.11.24.14



800.246.LEAK (5325)  
info@greenfielddirect.com

